



### House Calls for Industrial WasteWater

**Aquapure™ B-CAT - RTU**

**Product Code: 2601098**  
**Revised Date: March 19, 2015**

### **Aquapure™ B-CAT- RTU**

**Aquapure™ B-CAT-RTU** is a liquid cationic polymer that has been pre-diluted for immediate use. It has a high charge density and is designed to enhance liquid/solid separation in a wide variety of industrial applications. It works well on organics and bio-waste. It also has the ability to break oil/water emulsions. **Aquapure™ B-CAT- RTU** is designed to mass precipitate so that it will settle rapidly. **Aquapure™ B-CAT- RTU** is often used in batch or continuous type tanks.

#### **Aquapure™ B-CAT - RTU APPLICATIONS**

- Primary Clarification
- Sludge Dewatering
- Paper Recycle Clarification
- Secondary Clarification
- Sludge Thickening
- Emulsion Breaker

**Aquapure™ B-CAT-RTU** is often best used in conjunction with other Aquapure products to accomplish the needed tasks.

#### **PREPARATION**

**Aquapure™ B-CAT- RTU** is at working concentration and should be used as received. Dosing should be determined case by case using jar testing as a guide.

#### **PH CONTROL**

Precipitating and coagulating reagents are most effective in the range of pH 7.0 – 9.0. Since this is the general range for acceptable discharge to sewer, adjust the pH prior to adding water treatment products.



## Product Bulletin

### House Calls for Industrial WasteWater

**Aquapure™ B-CAT - RTU**

**Product Code: 2601098**  
**Revised Date: March 19, 2015**

### **STORAGE AND HANDLING**

**DO NOT FREEZE** Aquapure™ B-CAT- RTU. Aquapure™ B-CAT-RTU should be stored in a cool area and protected from freezing. The shelf life of the Aquapure™ B-CAT- RTU is 30 days and is made to order. Product is not returnable.

Spilled product should be scooped up as much as possible and the remaining layer absorbed with a material such as sweeping compound. Follow all federal, state and local regulations in clean up and disposal of spilled product.

**Do not** use aluminum, copper or mild steel tanks, pumps or piping.

### **WARRANTY**

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.